

POWER PUMPS

G3 Series - Electric

SIMPLEX



G3132 Shown

Reservoir Capacity► 1 - 20 gallons

Flow @ Rated Pressure► 46 cu.in./min.

Maximum Pressure► 10,000 psi

- Powered by a 115V - 60Hz, 1.13 hp universal motor (21,000 rpm).
- Low startup voltage, draws 16 amps at full load (230V models available).
- Equipped with a 15' remote power controlled pendant.
- Reservoirs available in 1- 20 gallons; welded steel design.
- Ideal for use with small, mid sized hydraulic cylinders or tools.

Power Pumps



SITE GAUGE

Metal reservoir site gauge for easy viewing of oil level.



IN-LINE VALVES - page 72

Maximize control and safety with our in-line valves.



MANIFOLDS - page 73

The ideal solution in obtaining precise control when operating multiple cylinders.



SUC-O-MATIC VALVE


The 3 position / 3 way "Suc-O-Matic" valve draws hydraulic oil out of any single acting cylinder with full retraction regardless of weak springs or mounting.



THINK SAFETY

Please refer to pages 4&5 for a complete list of safety tips and recommendations.

A Simplex G3 power pump was used at a testing facility to pressurize manifolds for leaks. ▼





Model	Pressure Rating (psi)		Output Flow (cu.in./min.)		Motor Spec.		Valve Type	Pendant Control	Usable Oil	Weight (lbs)
	1st Stage	2nd Stage	1st Stage	2nd Stage	(vac)	(amps)				
G3100	1,100	10,000	525	46	115	16	Dump	Motor	1	38
G3101	1,100	10,000	525	46	115	16	Dump	Motor	1	45
G3102	1,100	10,000	525	46	115	16	Dump	Motor	1.5	50
G3121	1,100	10,000	525	46	115	16	2W, 2P	Motor	1	45
G3122	1,100	10,000	525	46	115	16	2W, 2P	Motor	1.5	52
G3131	1,100	10,000	525	46	115	16	3W, 3P	Motor	1	48
G3132	1,100	10,000	525	46	115	16	3W, 3P	Motor	1.5	53
G3133	1,100	10,000	525	46	115	16	3W, 3P	Motor	2.5	63
G3162	1,100	10,000	525	46	115	16	3W, 3P	Motor / Solenoid	1.5	57
G3163	1,100	10,000	525	46	115	16	3W, 3P	Motor / Solenoid	2.5	67
G3141	1,100	10,000	525	46	115	16	4W, 3P	Motor	1	48
G3142	1,100	10,000	525	46	115	16	4W, 3P	Motor	1.5	53
G3143	1,100	10,000	525	46	115	16	4W, 3P	Motor	2.5	63
G3172	1,100	10,000	525	46	115	16	4W, 3P	Motor / Solenoid	1.5	57
G3173	1,100	10,000	525	46	115	16	4W, 3P	Motor / Solenoid	2.5	67

Power Pumps

	MODEL	SELECTIONS
Class	G	Power Pump
Series	3	1.13 HP Universal Motor / 46 cu.in.
Motor Voltage	1	1 = 115 VAC Single Phase 2 = 230 VAC Single Phase
Valve Function	3	<div>0 = Dump</div> <div>1 = 2 Way Dump</div> <div>2 = 2 Way Manual</div> <div>3 = 3 Way Manual</div> <div>4 = 4 Way Manual</div> <div>5 = 5 Gallons Usable Oil</div> <div>6 = 3 Way Solenoid</div> <div>7 = 4 Way Solenoid</div>
Reservoir Size	2	<div>1 = 1 Gallon Usable Oil</div> <div>2 = 1.5 Gallons Usable Oil</div> <div>3 = 2.5 Gallons Usable Oil</div> <div>5 = 5 Gallons Usable Oil</div> <div>6 = 10 Gallons Usable Oil</div> <div>7 = 20 Gallons Usable Oil</div>
Factory Installed Options*	G	<div>C = Caster Wheel Kit</div> <div>F = Foot Switch (Motor)</div> <div>G = Pump Mounted Gauge</div> <div>L = Locking Style Manifold</div> <div>O = Oil Filter</div> <div>P = Pressure Switch</div> <div>R = Roll Cage</div> <div>S = Foot Switch (Valve)</div>

* Oil filter not available on dump, 2 way dump & 2 way manual.