

# POWER PUMPS

G4 Series - Electric



G4173 Shown

Reservoir Capacity .....▶ 15 - 20 gallons

Flow @ Rated Pressure .....▶ 55 cu.in./min.

Maximum Pressure .....▶ 10,000 psi

- ▶ Powered by a 115V - 60Hz, 1.5 hp induction motor (1,725 rpm).
- ▶ Low startup voltage, draws amps at full load (230V models available).
- ▶ High performance two-stage pump provides higher cross-over pressure for faster cycle times and equipment operation.
- ▶ Ideal for use with mid sized hydraulic cylinders.

Power Pumps



### CYLINDERS - pages 7 - 29

A large selection of steel and aluminum cylinders to meet every need.



### COUPLERS - pages 74 - 75

High flow quick disconnect couplers provide a quick change to a variety of pumps.



### MANIFOLDS - page 73

The ideal solution in obtaining precise control when operating multiple cylinders.



### SUC-O-MATIC VALVE

*The 3 position / 3 way "Suc-O-Matic" valve draws hydraulic oil out of any single acting cylinder with full retraction regardless of weak springs or mounting.*



### THINK SAFETY

Please refer to pages 4&5 for a complete list of safety tips and recommendations.

The Simplex G4 power pump along with the S3000A spreader was used to pry apart the rusted doors on this steel shipping container. ▼



