

# Locknut Cylinders

Home / Cylinders / Locknut Cylinders / Single Acting Locknut Cylinders / 100 Ton Capacity / 100 Ton Locknut Cylinder, 6.00" Stroke



## 100 Ton Locknut Cylinder, 6.00" Stroke

### SN1006

- Single acting cylinder with mechanical safety lock nut
- Designed to support and hold loads without hydraulic pressure
- Load return
- 10,000 psi/700 bar maximum working pressure
- 3/8" NPTF female coupler and dust cap on all models

Categories: Single Acting Locknut Cylinders, Cylinders, 100 Ton Capacity, Locknut Cylinders

### Description

Rated Capacity (tons)	100
Stroke (in.)	6.00
Model #	SN1006
Cylinder Effective Area (in. <sup>2</sup> )	20.5
Oil Capacity (in. <sup>3</sup> )	123
Collapsed Height (in.)	11.35
Extended Height (in.)	17.35
Outside Diameter (in.)	6.5
Cylinder Bore Dia. (in.)	5.11
Plunger Diameter (in.)	5.12
Base to Coupler Port (in.)	1.2
Saddle Distance above Cylinder (in.)	0.1
Saddle Diameter (in.)	2.8
Weight (lbs.)	103

© 2017 Freedom Industrial Hydraulics. All rights reserved.

